

AD-A205 741

FTD-ID(RS)T-1067-88


## FOREIGN TECHNOLOGY DIVISION



LASER PHOTOELECTRIC EFFECT AT SURFACE OF DISCHARGE CATHODE

by

Gui Zhenxing, Zhang Shunye, et al.



FEB 28 1989

Approved for public release;  
Distribution unlimited.

## HUMAN TRANSLATION

FTD-ID(RS)T-1067-88

24 January 1989

MICROFICHE NR: FTD-89-C-000054

LASER PHOTOELECTRIC EFFECT AT SURFACE OF  
DISCHARGE CATHODE

By: Gui Zhenxing, Zhang Shunye, et al.

English pages: 2

Source: Zhongguo Jiguang, Vol. 13, Nr. 9,  
1986, pp. 590

Country of origin: China

Translated by: Leo Kanner Associates  
F33657-88-D-2188

Requester: ASD/FTD/TQIA

Approved for public release; Distribution unlimited.



THIS TRANSLATION IS A RENDITION OF THE ORIGINAL FOREIGN TEXT WITHOUT ANY ANALYTICAL OR EDITORIAL COMMENT. STATEMENTS OR THEORIES ADVOCATED OR IMPLIED ARE THOSE OF THE SOURCE AND DO NOT NECESSARILY REFLECT THE POSITION OR OPINION OF THE FOREIGN TECHNOLOGY DIVISION.

PREPARED BY:

TRANSLATION DIVISION  
FOREIGN TECHNOLOGY DIVISION  
WPAFB, OHIO.

#### GRAPHICS DISCLAIMER

All figures, graphics, tables, equations, etc. merged into this translation were extracted from the best quality copy available.

## LASER PHOTOELECTRIC EFFECT AT SURFACE OF DISCHARGE CATHODE

Gui Zhenxing, Zhang Shunye,  
Shen Guirong and Wang Runwen

Shanghai Institute of Optics and Precision Instruments

The photoelectric effect is produced by a glow discharge cathode irradiated by a continuous CO laser; this photoelectric effect is not related to the frequency of incident light (that is nonresonant absorption photoelectric current) but is only proportional to the intensity of incident light. Moreover, the photocurrent produced by a unit of light intensity is very sensitive to discharge current, gas composition, and gas pressure. A high temperature photoelectron emission mechanism at the cathode surface is described. *Chinese Journal of Optics, 1981, 12, 1*

(1) In a gas discharge, the positive ions bombard the cathode surface causing an instantaneous temperature rise at the surface microzone up to the melting and vaporization point temperatures; large numbers of high dynamic energy electrons exist in the microzone.

(2) Some high energy electrons absorb incident photons and escape outside of the metal surface, thus causing photoelectron emission.

(3) Due to the multiflow effect of the gas, photons at cathode surface are amplified into the photocurrent.

The theory can be better illustrated by the experimental results.

Using a direct heating type filament vacuum diode irradiated by a CO laser, the authors also detected a photocurrent. This finding further proves the occurrence of red shift effect of photoelectric emission frequency with rise in metal surface temperature.

It is pointed out that the photoelectric emission of discharge cathode can be possibly utilized as a type of photoelectric receiver. (207)

# DISTRIBUTION LIST

## DISTRIBUTION DIRECT TO RECIPIENT

<u>ORGANIZATION</u>	<u>MICROFICHE</u>
A205 DMAHTC	1
A210 DMAAC	1
C509 BALLISTIC RES LAB	1
C510 R&T LABS/AVEADCOM	1
C513 ARRADCOM	1
C535 AVRADCOM/TSARCOM	1
C539 TRASANA	1
C591 FSTC	4
C619 MIA REDSTONE	1
D008 MISC	1
E053 HQ USAF/INET	1
E404 AEDC/DOF	1
E408 AFWL	1
E410 AD/IND	1
E429 SD/IND	1
P005 DOE/ISA/DDI	1
P050 CIA/OCR/ADD/SD	2
AFTI/LDE	1
FTD	
CCF	1
MIA/PHS	1
LLYL/CODE L-389	1
NASA/NST-44	1
NSA/T513/TDL	2
ASD/FTD/TOLA	1
FSL/TEX-3	1